Technical Data Sheet
Allcosil 200

Introduction:

Allcosil 200 is a 200 centistoke polydimethylsiloxane silicone oil.

Uses:

- Release agent.
  Used purely or as a part of a compounded formula **Allcosil 200** provides a non-toxic, non-carbonising mould release for rubber, plastics and metal die-castings.
- Anti-foam agent.
  Very small quantities of the fluid are very effective as a foam control agent, especially in non-aqueous systems.
- Mechanical fluid.
  The very high viscosity-index, the thermal and chemical stability, shear-breakdown resistance and the rubber compatibility as well as the compressibility make this fluid outstanding for mechanical and hydraulic uses.
- Lubricant.
  The fluid provides excellent lubricating properties for most plastic and elastomeric surfaces. Lubricity with metals depends upon the possible combinations such as P.T.F.E., MoS2 and other lubricity improvers.
- In polishes and chemical specialties.
  Silicone oil is used in most automobile and furniture polishes for its ease of application, high gloss with a minimum rubbing and durable water repellent film.
- In electrical and electronic equipment. Because of the excellent dielectric properties silicone oil is widely used as an insulating and damping fluid.

Typical Characteristics:

Product Description			
	Appearance	Clear liquid	
	Odour	Characteristic	
Composition			
	Substance	**% by Weight**	
	Polydimethylsiloxane	100	
Properties			
	Property	**Unit**	**Value**
	Viscosity	cSt	200
	Flashpoint	°C COC	>300
	Freezing Point	°C	-50
	Specific gravity @ 25°C		0.970
	Surface tension	mN/m	21.0
	Refractive index		1.403

Features and Benefits:

Features:

- Little change in physical properties over a wide temperature range.
- The fluids are thermally stable at 150°C for extended time intervals.
- Excellent water repellence.
- Low surface tension. The fluid readily wets clean surfaces to impart water repellence and release characteristics.
- Low toxicity.

Allcosil Ltd.
Ambrose Street,
West Gorton,
Manchester, M12 5DD,
United Kingdom.

Registered in England and
Wales No: 16560414

Tel. 0161 223 7181
Fax. 0161 223 0173
Email: ja@allcocks.co.uk
Website: www.allcocks.co.uk

Technical Data Sheet
Allcosil 200

Benefits:

- Good foam builder
- Imparts soft silky feel to the hair
- Ensures smooth wet shaving foams
- Non-irritant to skin

Shelf Life:

Allcosil 200 has an unlimited useful life when stored at ambient temperatures. The product does not freeze and there are no restrictions on storage.

Packaging:

200-kilo, 20-kilo and 5-kilo, non-returnable plastic drums.

Health & Safety:

Detailed advice on the Health & Safety aspects of this product is given in the individual product Safety Data Sheet (SDS), available upon request.

Allcosil Ltd.
Ambrose Street,
West Gorton,
Manchester, M12 5DD,
United Kingdom.

Registered in England and
Wales No: 16560414

Tel. 0161 223 7181
Fax. 0161 223 0173
Email: ja@allcocks.co.uk
Website: www.allcocks.co.uk